

Saletto (LPPE)



Product Description

Sleek, clean look, low-profile panel convection heater with thermostat control, integral 7-day timer, open window detection and adaptive-start

Key Features

- Complies with Lot 20 of ERP Directive
- Low-profile Panel with upwards facing grille for optimum heat circulation
- Thermostat control provides room temperature stability to $\pm 0.2^{\circ}\text{C}$
- Splash-proof for use in bathrooms
- Suitable for domestic or commercial use

Dimensions

Technical Details

Construction	<ul style="list-style-type: none"> •Epoxy-polyester powder coated steel casing with upward-facing air outlet grille •Advanced Controls with cap-sense technology for total flexibility of heating
Controls	<ul style="list-style-type: none"> •Digitally controlled, Electronic •7 Day Programmable Timer Timer modes: <ul style="list-style-type: none"> •User Timer Continuous heat modes: <ul style="list-style-type: none"> •Timer, Manual, Frost Protect, Off
Controller UI	<ul style="list-style-type: none"> •Segmented Display with White Backlight •Capacitive buttons with Audio Feedback •User replaceable battery (Coin-Type)
Controller Functions	<ul style="list-style-type: none"> •Adaptive-Start •Adjustable SP range ($7-32^{\circ}\text{C}$)
Thermostat	Electronic Thermostat ($\pm 0.2^{\circ}\text{C}$)
Element	Compact, finned, mineral filled sheathed element
Installation	1 H-frame wall bracket for easy fixing
Safety	Thermal cut-out. Auto rest type
IP Rating	IP24
Class	Class I, with earth wire
Cable	1.3 metres fitted, 3 core, 1/N/PE ~230-240 V, 50Hz
Colour / Finish	Metal Chassis, Air Outlet Grille & Control Moulding - Traffic White (RAL 9016)

Warranty & Analysis

Approvals	CE
Warranty	1 Year
Country of Origin	United Kingdom
Manufacturer	Glen Dimplex Heating & Ventilation

Drawing Required

Model/Item No. (EAN-Code 5011139+Item No.)	091246	LPP050E 091239	LPP075E 091253	LPP100E 091260	LPP150E
Output (kW)	0.50	0.75	1.00	1.50	
Height (mm)	235	235	235	235	
Width (mm)	746	746	877	1142	
Depth (mm)	100	100	100	100	
Weight (KG)	6.7	6.7	7.6	9.9	
Packaging Details					
Height (mm)	000	000	000	000	
Width (mm)	000	000	000	000	
Depth (mm)	000	000	000	000	
Packed Weight (KG)	000	000	000	000	
Ti	000	000	000	000	
Hi	000	000	000	000	
Pallet Quantity (2.4m high)	000	000	000	000	