

DHB-E 18/21/24 LCD

CONVENIENCE INSTANTANEOUS WATER
HEATER

PRODUCT-NO.: 236745

DHB-E LCD instantaneous water heater – 3i comfort, as good as first class

On the DHB-E LCD instantaneous water heater, the water temperature is continuously electronically controlled by three sensors with 3i technology. This makes temperature fluctuations a thing of the past and ensures accurate temperature delivery up to the maximum output, making showering a delight every time.

With the LCD of the DHB-E LCD comfort instantaneous water heater, accurate temperature settings are no longer a problem. The rotary selector quickly enables accurate temperature delivery between 20 and 60 °C.



The main features

Electronically controlled instantaneous water heater

3i technology for accurate temperature delivery up to maximum output

Selectable output 18/21/24 kW in a single appliance

LCD with temperature display

For supplying several draw-off points with DHW

Precise temperature selection via rotary selector

Anti-scalding protection due to permanent 43 °C limit

Can be combined with FFB 4 (Set) EU wireless remote control



Type	DHB-E 11/13 LCD	DHB-E 18/21/24 LCD Set	DHB-E 18/21/24 LCD LCD Set
Part no.	236743	203866	236745
Rated output	11/13,5 kW	18/21/24 kW	18/21/24 kW
Width	225 mm	225 mm	225 mm
Height	466 mm	466 mm	466 mm
Depth	116 mm	116 mm	116 mm

Technical data

Rated voltage	400 V	400 V	400 V
Phases	3/PE	3/PE	3/PE
Frequency	50/60 Hz	50/60 Hz	50/60 Hz
Rated current	17,5/19,5 A	29/31/35 A	29/31/35 A
Fuses	20 A	32/32/35 A	32/32/35 A
Temperature adjustment	Off, 20-60 °C	Off, 20-60 °C	Off, 20-60 °C
Specific conductivity $\sigma_{15} \leq$	1111 $\mu\text{S}/\text{cm}$	1111 $\mu\text{S}/\text{cm}$	1111 $\mu\text{S}/\text{cm}$
Specific resistance $\rho_{15} \geq$	900 $\Omega \text{ cm}$	900 $\Omega \text{ cm}$	900 $\Omega \text{ cm}$
Energy efficiency class	A	A	A
Colour	white	white	white
IP-Rating	IP25	IP25	IP25
Weight	2,8 kg	2,9 kg	2,9 kg



Type	DHB-E 27 LCD Set
Part no.	203865
Rated output	18/21/24 kW
Width	225 mm
Height	466 mm
Depth	116 mm

Technical data

Rated voltage	400 V
Phases	3/PE
Frequency	50/60 Hz
Rated current	29/31/35 A
Fuses	32/32/35 A
Temperature adjustment	Off, 20-60 °C
Specific conductivity $\sigma_{15} \leq$	1111 $\mu\text{S}/\text{cm}$
Specific resistance $\rho_{15} \geq$	900 $\Omega \text{ cm}$
Energy efficiency class	A
Colour	white
IP-Rating	IP25
Weight	2,9 kg

Contact information

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 346 2300

Or send an e-mail to

sales@stiebel-eltron.co.uk

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.