

DHB-E 27 LCD Set

CONVENIENCE INSTANTANEOUS WATER
HEATER

PRODUCT-NO.: 203865

The main features

Pivoting appliance cover and programming unit for increased operating convenience on undersink installations

Precise temperature selection via rotary selector

Suitable for reheating preheated water up to 55 °C (maximum inlet temperature 70 °C)

LCD with temperature display

Electronic output control with 3i technology for maximum energy efficiency and accurate temperature delivery

Quick PROFI-RAPID installation

Selectable output 18/21/24 kW in a single appliance





Type	DHB-E 11/13 LCD	DHB-E 18/21/24 LCD Set	DHB-E 18/21/24 LCD
Part no.	236743	203866	236745
Rated output	11/13,5 kW	18/21/24 kW	18/21/24 kW
Width	225 mm	225 mm	225 mm
Height	466 mm	466 mm	466 mm
Depth	116 mm	116 mm	116 mm

Technical data

Rated voltage	400 V	400 V	400 V
Phases	3/PE	3/PE	3/PE
Frequency	50/60 Hz	50/60 Hz	50/60 Hz
Rated current	17,5/19,5 A	29/31/35 A	29/31/35 A
Fuses	20 A	32/32/35 A	32/32/35 A
Temperature adjustment	Off, 20-60 °C	Off, 20-60 °C	Off, 20-60 °C
Specific conductivity $\sigma_{15} \leq$	1111 $\mu\text{S}/\text{cm}$	1111 $\mu\text{S}/\text{cm}$	1111 $\mu\text{S}/\text{cm}$
Specific resistance $\rho_{15} \geq$	900 $\Omega \text{ cm}$	900 $\Omega \text{ cm}$	900 $\Omega \text{ cm}$
Energy efficiency class	A	A	A
Colour	white	white	white
IP-Rating	IP25	IP25	IP25
Weight	2,8 kg	2,9 kg	2,9 kg



Type	DHB-E 27 LCD Set
Part no.	203865
Rated output	18/21/24 kW
Width	225 mm
Height	466 mm
Depth	116 mm

Technical data

Rated voltage	400 V
Phases	3/PE
Frequency	50/60 Hz
Rated current	29/31/35 A
Fuses	32/32/35 A
Temperature adjustment	Off, 20-60 °C
Specific conductivity $\sigma_{15} \leq$	1111 $\mu\text{S}/\text{cm}$
Specific resistance $\rho_{15} \geq$	900 $\Omega \text{ cm}$
Energy efficiency class	A
Colour	white
IP-Rating	IP25
Weight	2,9 kg

Contact information

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 346 2300

Or send an e-mail to

sales@stiebel-eltron.co.uk

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.