


CND 150

CONVECTOR HEATERS

PRODUCT-NO.: 234815

APPLICATION: Wall mounted heat wave convector as an efficient heating system for spring and autumn and for additional heat demand in the living space, bathroom, hallway or in utility rooms. The two integrated heating systems for radiant heating and convection heating ensure a pleasant and cosy room temperature. The elegant and minimalist design blends into any modern setting.



EQUIPMENT / CONVENIENCE: Designer radiator with 2 heating systems and precise electronic control with intelligent energy saving functions. When the window is open, the appliance automatically switches to frost protection mode; the motion sensor recognises when nobody is left inside the room and automatically lowers the set room temperature. The 7-day timer offers 3 preset time programs that can be individually adjusted to suit current requirements.

INSTALLATION / SERVICE: Straightforward and stable wall mounting by one person only. The appliance is connected using a permanent power supply. Maintenance free.

SAFETY: Integral high limit safety cut-out and omnipolar ON/OFF switch.

The main features

Modern and high grade design

Controls with backlit LCD

7-day timer, frost protection and open window detection

ON/OFF switch and overheating protection



Type	CND 75	CND 100	CND 150
Part no.	234813	234814	234815
Connected load	0,75 kW	1 kW	1,5 kW
Height	504 mm	504 mm	504 mm
Depth	120 mm	120 mm	120 mm
Width	675 mm	790 mm	1010 mm

Technical data

Power supply	1/N ~ 230 V	1/N ~ 230 V	1/N ~ 230 V
Frequency	50/- Hz	50/- Hz	50/- Hz
Rated voltage	230 V	230 V	230 V
Rated current	3,3 A	4,3 A	6,5 A
Weight	6,7 kg	7,7 kg	9,7 kg
Colour	white, RAL 9010	white, RAL 9010	white, RAL 9010
Setting range	10 - 30 °C	10 - 30 °C	10 - 30 °C
IP-Rating	IP24	IP24	IP24
Protection class	II	II	II



Type	CND 200
Part no.	234816
Connected load	2 kW
Height	504 mm
Depth	120 mm
Width	1240 mm

Technical data

Power supply	1/N ~ 230 V
Frequency	50/- Hz
Rated voltage	230 V
Rated current	8,7 A
Weight	11,5 kg
Colour	white, RAL 9010
Setting range	10 - 30 °C
IP-Rating	IP24
Protection class	II

Contact information

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 346 2300

Or send an e-mail to

sales@stiebel-eltron.co.uk

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.