

# SN 15 SL GB

SMALL WATER HEATERS 5 TO 15 L

PRODUCT-NO.: 227682

For the installation of the small water heater above the draw-off point, the small water heater SN..SL is ideal for the supply of a single draw-off point. These devices are available with capacities from 5 to 15 litres. Their temperature can be selected anywhere between 35 °C and 85 °C, making water with a consistent temperature available at all times. The thermal cut-out provides a permanent, safety-first maximum water temperature. This can be set to 38, 45, 55 or 65 °C. The highly effective thermal insulation of the small water heaters ensures the lowest energy losses.



## The main features

Small water heater, 15 litre capacity

---

For a single draw-off point

---

Extremely large amount of mixed water

---

Low standby loss power consumption

---

Economy setting 60 °C

---

Splashproof to IP 24

---

Power cable for permanent connection, approx. 1 m



Type	SN 15 SL 3.3 kW	SN 5 SL GB	SN 10 SL GB
Part no.	222203	221125	222192
Connected load	3,3 kW	2 kW	2 kW
Height	601 mm	421 mm	503 mm
Width	316 mm	263 mm	295 mm
Depth	295 mm	230 mm	275 mm

#### Technical data

Rated voltage 1	220 V	220 V	220 V
Rated output 1	3,0 kW	1,8 kW	1,8 kW
Rated current 1	13,7 A	8,3 A	8,3 A
Fuse 1	16 A	10 A	10 A
Rated voltage 2	230 V	230 V	230 V
Rated output 2	3,3 kW	2,0 kW	2,0 kW
Rated current 2	14,3 A	8,7 A	8,7 A
Fuse 2	16 A	10 A	10 A
Rated voltage 3	240 V	240 V	240 V
Rated output 3	3,6 kW	2,2 kW	2,2 kW
Rated current 3	15,0 A	9,1 A	9,1 A
Fuse 3	16 A	10 A	10 A
Frequency	50/60 Hz	50/60 Hz	50/60 Hz
Phases	1/N/PE	1/N/PE	1/N/PE
Rated capacity	15 l	5 l	10 l
Power supply	1/N/PE	1/N/PE	1/N/PE
Standby energy consumption/24 h at 65 °C	0,37 kWh	0,20 kWh	0,30 kWh
Colour	white	white	white

<b>IP-Rating</b>	IP24 D	IP24 D	IP24 D
<b>Energy efficiency class</b>	A	A	A
<b>Weight</b>	6,1 kg	3,2 kg	5,1 kg



Type	<b>SN 15 SL GB</b>
Part no.	227682
Connected load	3,3 kW
Height	601 mm
Width	316 mm
Depth	295 mm

#### Technical data

Rated voltage 1	220 V
Rated output 1	3,0 kW
Rated current 1	13,7 A
Fuse 1	16 A
Rated voltage 2	230 V
Rated output 2	3,3 kW
Rated current 2	14,3 A
Fuse 2	16 A
Rated voltage 3	240 V
Rated output 3	3,6 kW
Rated current 3	15 A
Fuse 3	16 A
Frequency	50/60 Hz
Phases	1/N/PE
Rated capacity	15 l
Power supply	1/N/PE
Standby energy consumption/24 h at 65 °C	0,37 kWh
Colour	white

<b>IP-Rating</b>	IP24 D
<b>Energy efficiency class</b>	A
<b>Weight</b>	6,1 kg

oversink water heater pack that comes complete with inlet valve and outlet spout

---

**Contact information**

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 346 2300

Or send an e-mail to

[sales@stiebel-eltron.co.uk](mailto:sales@stiebel-eltron.co.uk)

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.